



# SLA/AGM BATTERIES

**Werker SLA technology offers high-density power that out-performs traditional lead acid batteries. The Absorbed Glass Mat (AGM) construction is designed for efficient gas recombination and allows for maintenance-free operation. Werker SLA batteries maintain their high capacity with a design that is resistant to damage caused by deep discharge. Every Werker SLA battery is inspected to ensure the highest standards in materials and fabrication.**

### **Battery Features:**

- Werker SLA AGM batteries contain a proprietary grid alloy formula. This formula combined with the advanced plate curing techniques offer improved performance.
- Werker batteries contain a unique electrolyte formula with a special sub-colloid additive for higher reliability and longer life.
- More than 1,000 discharge/recharge cycles.
- The unique construction and sealing techniques of the Werker battery guarantee leak-proof operation.
- Heavy-duty lead calcium tin alloy grids provide an extra margin of performance and service life in cyclic applications, even after repeated over-discharges.
- Quality Assurance Engineers monitor and control the entire production process.

### **Charger Features:**

#### **New! SLA Chargers**

- Regulated trickle charge for "float" mode charging
- Short circuit protected
- Reverse polarity protected
- Thermal protection in case of overload
- Alligator clips
- Color LED to indicate state of charger



SLA/AGM BATTERIES													
Item #	Volts	Flame Retardant	Capacity Ah	Dimensions L x W x H (in.)	Height Over Terminal (in.)	Weight (lbs.)	Item #	Volts	Flame Retardant	Capacity Ah	Dimensions L x W x H (in.)	Height Over Terminal (in.)	Weight (lbs.)
<a href="#">WKA12-0.8WL</a>	12	-	0.8	3.78 x 0.98 x 2.40	2.4	0.8	<a href="#">WKA12-7.5F2</a>	12	-	7.5	5.94 x 2.56 x 3.74	3.98	6.0
<a href="#">WKA12-1.3F</a>	12	-	1.3	3.82 x 1.69 x 2.05	2.28	1.4	<a href="#">WKA12-12F2</a>	12	-	12	5.94 x 3.90 x 3.74	3.98	9.3
<a href="#">WKA12-2ST</a>	12	-	2	5.91 x 0.79 x 3.54	3.54	1.7	<a href="#">WKA12-18NBL</a>	12	-	18	7.13 x 3.03 x 6.57	6.57	13.9
<a href="#">WKA12-2.3F</a>	12	-	2.3	6.97 x 1.38 x 2.40	2.64	2.0	<a href="#">WKA12-26NB</a>	12	-	26	6.50 x 6.93 x 4.92	4.92	20.3
<a href="#">WKA12-3.3F</a>	12	-	3.2	5.28 x 2.64 x 2.40	2.64	3.2	<a href="#">WKA12-33C</a>	12	-	35	7.72 x 5.16 x 6.10	6.57	25.4
<a href="#">WKA12-5.1A</a>	12	-	4.5	5.51 x 1.89 x 3.98	4.21	4.4	<a href="#">WKA12-33J</a>	12	-	35	7.72 x 5.16 x 6.10	7.09	25.4
<a href="#">WKA12-5F</a>	12	-	5	3.54 x 2.76 x 3.98	4.21	4.0	<a href="#">WKA12-44C/FR</a>	12	Y	45	7.80 x 6.54 x 6.85	6.85	35.7
<a href="#">WKA12-7.5F</a>	12	-	7.5	5.94 x 2.56 x 3.74	3.98	6.0	<a href="#">WKA12-55C/FR</a>	12	Y	60	9.02 x 5.43 x 8.19	8.35	40.3

Continued on Next Page

For more information please contact:

**ReplacementUPSbattery.com**  
Restore the Power for LESS!

www.ReplacementUPSbattery.com

Phone: 952-217-6611

Email: info@replacementupsbattery.com

# SLA/AGM BATTERIES

Item #	Volts	Flame Retardant	Capacity Ah	Dimensions L x W x H (in.)	Height Over Terminal (in.)	Weight (lbs.)	Item #	Volts	Flame Retardant	Capacity Ah	Dimensions L x W x H (in.)	Height Over Terminal (in.)	Weight (lbs.)
WKA12-55P/FR	12	Y	60	9.02 x 5.43 x 8.19	9.06	40.3	WKA6-14A	6	-	14	4.25 x 2.80 x 5.51	5.51	6.2
WKA12-80C/FR	12	Y	80	10.24 x 6.65 x 8.31	8.46	55.1	WKA6-14T1	6	-	14	4.25 x 2.80 x 5.51	5.51	6.2
WKA12-80J/FR	12	Y	80	10.24 x 6.65 x 8.31	9.06	55.1	WKA6-14T2	6	-	14	4.25 x 2.80 x 5.51	5.51	6.2
WKA12-100C/FR	12	Y	100	12.09 x 6.65 x 8.31	8.46	72.8	WKA6-14T3	6	-	14	4.25 x 2.80 x 5.51	5.51	6.2
WKA12-100J/FR	12	Y	100	12.09 x 6.65 x 8.31	9.06	72.8	WKA6-42F2	6	-	42	6.38 x 3.46 x 6.42	6.69	15.9
WKA12-125C/FR	12	Y	140	13.43 x 6.81 x 11.06	11.3	104.7	WKA6-42NB	6	-	42	6.38 x 3.46 x 6.42	6.85	15.9
WKA6-1.3F	6	-	1.3	3.82 x 0.94 x 2.05	2.28	0.7	WKA4-4.5F2	4	-	4.5	1.85 x 1.85 x 3.98	4.21	1.3
WKA6-3.3F	6	-	3.2	5.28 x 1.34 x 2.40	2.64	1.6	<b>WERKER SLA CHARGERS</b>						
WKA6-5F	6	-	5	2.76 x 1.85 x 3.98	4.21	2.1	<b>Item #</b>	<b>Volts</b>	<b>mA</b>	<b>Dimensions L x W x H (in.)</b>	<b>Weight (lbs.)</b>		
WKA6-5SP	6	-	5	2.64 x 2.64 x 3.82	4.53	2.0	<a href="#">WK6V500</a>	6V	500mA	2.36 x 2.04 x .73	0.58		
WKA6-7.2F	6	-	7.2	5.94 x 1.34 x 3.74	3.98	3.0	<a href="#">WK12V500</a>	12V	500mA	2.36 x 2.04 x .73	0.66		
WKA6-8.2F	6	-	8.2	3.90 x 2.24 x 4.53	4.53	3.8	<a href="#">WK6V1000</a>	6V	1000mA	2.54 x 2.32 x 1.95	0.86		
WKA6-10F	6	-	10	5.94 x 1.97 x 3.74	3.98	4.4	<a href="#">WK12V1000</a>	12V	1000mA	2.54 x 2.32 x 1.95	1.00		
WKA6-12F	6	-	12	5.94 x 1.97 x 3.74	3.98	4.6							
WKA6-12F2	6	-	12	5.94 x 1.97 x 3.74	3.98	4.6							